



AST F694HZZ deep groove ball bearings

Bearing No. F694HZZ

| | |
|--|-----------------------------|
| Size | 4x11x4 mm |
| Bore Diameter | 4 mm |
| Outer Diameter | 11 mm |
| Width | 4 mm |
| Bearing Type | Flange Shielded |
| Bore Dia (d) | 4.0000 |
| Outer Dia (D) | 11.0000 |
| Width (B) | 4.0000 |
| Radius (min) (rs) | 0.150 |
| Flange Dia (Df) | 12.5000 |
| Flange Width (Bf) | 1.000 |
| Dynamic Load Rating (Cr) | 814 |
| Static Load Rating (Cor) | 280 |
| Max Speed (Grease) (X1000 RPM) | 48 |
| Max Speed (Oil) (X1000 RPM) | 56 |
| Max. Shaft Shoulder Dia. Inner (Ui) | 5.6 |
| Min. Housing Shoulder Dia., Outer (Uo) | 9.850 |
| Ball Qty | 7 |
| Ball Dia (Dw) | 2.0000 |
| Weight (g) | 1.97 |
| Precision | A1 |
| Standard Clearance | K25 |
| Material | Martensitic Stainless Steel |

F694HZZ Bearing 2D drawings and 3D CAD models